Mr./Mrs./Ms.:							Model:							Reg. No.:							
Invoice/Job No.:						Odometer Reading:						_ ,	V.I.N.:								
Service type:	O	Α	O	В	0	Α	0	В	O	Α	O	В	0	Α	O	В	O	Α	O	В	ì
Months: ,000 km:	6 12	12 24	18 36	24 48	30 60	36 72	42 84	48 96	54 108	60 120	66 132	72 144	78 156	84 168	90 180	96 192	102 204	108 216	114 228	120 240	ı



DISCOVERY 4 / LR4 (NON 3.0 TDV6 TO 11MY REST OF WORLD)

Adjust/Lubricate/Replace - Labour cost included in scheduled time except items marked *
Check - After the checking procedure, cleaning, adjusting, repairing or replacing is subject to extra labour and material cost.

☐ Renew engine oil and filter

Check	- After	the checking procedure, cleaning, adjusting, repairing or replacing is subject to extra labour and ma	terial cos	st.		MAINTENANCE CHECK SHEET
	Oil	OIL SERVICE				MAIN SERVICE (UNDER VEHICLE)
1.		Renew engine oil and filter (Every 6 months / 12,000 km)	33.		240k	Renew manual gearbox oil (Every 10 years)
)		Renew fuel filter element (Diesel - Every 6 months / 12,000 km) - Chinese	34. 35.	10/		Renew automatic transmission oil and filter (Every 10 years)
		and Indian markets only Check battery condition and check/top-up battery electrolyte level (Every 6	36.	120	JK <u>240K</u>	Renew transfer box oil, replace drain and fill plugs and washers Renew front and rear axle oil <i>(Every 10 years)</i>
3.		months / 12,000 km) - MENA markets only	37.	120	Ok 240k	Renew locking differential oil
	Α	B MAIN SERVICE (VEHICLE INTERIOR)	38.			Check for free play in all suspension and body mounting rubbers
1.		Check condition and security of seats and seatbelts	39. 40.			Check condition of all suspension, driveshafts and steering boots and gaiters Replace all flexible brake hoses (Every 6 years)*
5.		Check operation of all lamps, horns and warning indicators	41.			Check visually brake servo hose, brake, fuel, PAS and clutch pipes, unions
3.		Check operation of front/rear wipers and washers and condition of wiper				and electrical harnesses for chafing, leaks and corrosion
_		blades Select the LOW range gears and drive the vehicle 3 to 4 vehicle lengths then	42. 43.		$\dashv \vdash$] Adjust the electric park brake shoes Check for fluid leaks
7.		re-select HIGH range gears	43. 44.		$\exists \vdash$	Check exhaust system for leaks, security and damage
3.		Replace pollen filter	45.			Check steering rod ball joint fixings and condition of ball joints and dust covers
		MAIN SERVICE (VEHICLE EXTERIOR)	46.			If fault lamp(s) are illuminated, interrogate that system using IDS\SDD and
9		Annual corrosion/cosmetic inspection - using annual corrosion inspection	47.		7 —	¹ report findings*] Carry out road test (see WARNING over page)
		sheet Check tyre pressures, condition and tread depth	48.			Reset service interval announcement indicator
10.		Officer tyre pressures, condition and tread depth	49.			Endorse service record
11.		Remove road wheels	50. 51.		$\exists \vdash$	Reset oil level indicator (if fitted) Check for any applicable outstanding service actions or recalls
12.		Inspect brake pads for wear, calipers for leaks and disks for condition	52.		-	Report any unusual features of vehicle condition and additional work required
13. 14.		Replace brake fluid <i>(Every 3 years)*</i> Renew fuel filter element <i>(Diesel)</i>				
15.		Renew fuel filter element (Diesel) - Chinese and Indian markets only				
16.		Drain fuel sedimentor (Diesel)				
17.		Refit road wheels to opposite sides of the same axle (Use anti-seize compound on spigot bore) Not vehicles fitted with uni-directional tyres				
		Check operation of door checks, bonnet catch & fuel flap and lubricate door				
18.		checks				
19.		Apply lubricant to door seals - Nordic markets only				
20.		Check condition of removable towbar				
14		MAIN SERVICE (UNDER BONNET)				
21. 22.		Check anti-freeze specific gravity Renew coolant (Every 10 years)				
23.	168k					
24.		144k Renew spark plugs (V6)				
25. 26.		240k Renew air cleaner element <i>(Petrol)</i> 144k Renew air cleaner element <i>(2.7L Diesel)</i>	The	main	tonance	e items listed, are those recommended for vehicles operating under normal driving,
27.	/2K	Check condition of ancillary driving belts				c conditions. More frequent attention may be necessary if the vehicle is subject to
28.		240k Renew ancillary driving belts (Every 10 years)	stop	/star	t operat	ion, extremes of temperature, dusty conditions, off road driving or frequent towing
29.	168k	Renew front and rear camshaft timing belts, tensioners and tensioner bolt	of tr			unloted commetic/correction inequation check completed and convice restfells have
30.		(2.7L Diesel Every 7 years) Check/top-up brake, PAS and clutch fluid levels and screen washer reservoirs	Serv			npleted, cosmetic/corrosion inspection check completed and service portfolio book
31.		Check/top-up battery electrolyte level - low maintenance battery fitted	0	u	-	
	Α	B MAIN SERVICE (UNDER VEHICLE)	Nam	ie:		Signature: Date:

JLR 14 70 21_2E 7/10/2010

WARNING: Two wheel roller tests must not be carried out. Four wheel roller tests must be limited to 5 km/hour (3 miles/hour).

IMPORTANT - OIL CHANGE DIESEL ENGINES

If the vehicle is operated on fuel with a high sulphur content (over 0.7) the oil change intervals must not exceed 6,000Km (3750 miles)

If the vehicle is operated on fuel with a moderate sulphur content (between 0.3 - 0.7) the oil change intervals must not exceed 12,000Km (7500 miles)

IT IS RECOMMENDED THAT:

Comments/Remedial Work

After 80 km continuous use in severe off road conditions - wading, deep mud and abrasive grit/slurry - the electric park brake should be inspected, cleaned and adjusted, and the ancillary drive belt should be inspected and cleaned.

Air suspension vehicles used extensively in arduous/ off road conditions will require the compressor inlet filter to be replaced at more regular intervals.

When the vehicle is used in dusty or field conditions or deep wading, frequent attention to the air cleaner may be required.

When the vehicle is used in areas where fuel quality is poor, more frequent draining of the fuel filter/ sedimentor may be required.

For full details regarding the operations contained in this maintenance check sheet, please refer to the workshop manual.

GLOSSARY:

OIL SERVICE = The oil service is applicable to all vehicles. It is carried out at 6 month or 12,000 km intervals, whichever occurs first.

MAIN SERVICE = The main service is applicable to all vehicles. It is carried out at 12 month or 24,000 km intervals, whichever occurs first.

Main Service "A" is applicable at 12 months/24,000 km, 36 months/72,000 km, 60 months/120,000 km 84 months/168,000 km and so on.

Main Service "B" is applicable at 24 months/48,000 km, 48 months/96,000 km, 72 months/144,000 km, 96 months/192,000 km and so on. Some items do not need to be carried out at every main service and these items are identified by an indicator in the tick box e.g. 60k (This indicates that this item is only applicable every 60,000 km)

NOTE: The service required should be at the time or distance stated, which ever occurs first.