

AUTOMOTIVE LUBRICANTS

FormulaShell* Multi-Vehicle Automatic Transmission Fluid

1.34

FormulaShell Multi-Vehicle Automatic Transmission Fluid is a specially formulated fluid designed to meet the requirements of a broad range of automatic transmission specifications. FormulaShell Multi-Vehicle is a special blend of high quality base stocks with an advanced additive system for automatic and powershift transmissions. FormulaShell Multi-Vehicle protects against shudder, eliminates the need to stock ATF supplements and ensures a high-performance smooth driving experience. FormulaShell Multi-Vehicle is recommended for use in most North American vehicles. It is not suitable in a few pre-1986 vehicles where Type F fluids were specified, vehicles requiring Dexron VI† fluids or some recent vehicles equipped with continuous variable transmissions (CVT's), for exact requirements please consult your vehicle owners manual.

Applications:

 FormulaShell Multi-Vehicle is suitable for use in vehicles that require the following specifications:

 GM Dexron†, Dexron† II, GM Dexron† IIE and Dexron† III

• Type A and Type A Suffix

• Ford Mercon†† and Mercon††V

• Chrysler Automatic Transmissions (ATF +3 and +4†††)

Allison C-4

• Caterpillar TO-2

FormulaShell Multi-Vehicle is also suitable for all models of the following Auto Makers vehicles: Acura, AM General (Hummer), Buick, Cadillac, Chevrolet, Dodge, Daewoo, Eagle, Ford Auto, Geo, GMC Trucks, Honda, Hyundai, Isuzu, Jeep, KIA, Landrover, Lincoln, Mazda, Mercury, Mitsubishi, Oldsmobile, Plymouth, Pontiac, Scion, Subaru, Suzuki and Volkswagen

†Registered trademark of General Motors Corporation

††Copyright of Ford Motor Company

34

 $\verb| ††| Trademark of Daimler Chrysler Corporation|$

Engine Oils





AUTOMOTIVE LUBRICANTS

FormulaShell* Multi-Vehicle Automatic Transmission Fluid

1.34

Typical Properties:

FORMULASHELL MULTI-VEHICLE	
Product Code	425-109
Colour	Red
Viscosity Index	185
Viscosity, cSt @ 40°C @ 100°C	35.0 7.4
Brookfield Viscosity, cP @ -40°C	11,000
Flash Point, COC, °C	190
Pour Point, °C	-45

Engine Oils 35