



TECHNICAL BULLETIN

No: LTB00205
Issue: 1
Date: 06 MAY 2009

CIRCULATE TO:

Service Mgr
X

Warranty
X

Workshop
X

Body Shop

Parts
X

SECTION: 206

'Chirp' or 'Squeal' Noise from Rear Brakes While Slowly Moving Forward and Lightly Braking - Repair Procedure

AFFECTED VEHICLE RANGE:

LR3 (LA)

VIN: 5A000303 - 9A507637

Model Year: 2005 - 2009

Range Rover Sport (LS)

VIN: 6A900290 - 7A999999

7A100001 - 9A207274

Model Year: 2006 - 2009

CONDITION SUMMARY:

Situation: With the brakes at normal operating temperature, a high-pitched 'chirp' noise may be heard once per wheel revolution while slowly driving forward and lightly applying the brakes. This noise may be due to the rear brake pads.

Action: In the event of a customer concern of the above, refer to the Repair Procedure below to replace the rear brake pads.

PARTS:

LR016808Rear brake pads Qty: 1

TOOLS:

Refer to Workshop Manual (GTR) for any required special tools

WARRANTY:



NOTE: Repair procedures are under constant review, and therefore times are subject to change; those quoted here must be taken as guidance only. Always refer to DDW to obtain the latest repair time.

DDW requires the use of causal part numbers. Labor only claims must show the causal part number with a quantity of zero.

Description	SRO	Time (hours)	Condition Code	Causal Part
Install rear brake pads	70.40.03	0.60	42	LR016808

Normal warranty policy and procedures apply.

NOTE: The information in Technical Bulletins is intended for use by trained, professional Technicians with the knowledge, tools, and equipment required to do the job properly and safely. It informs these Technicians of conditions that may occur on some vehicles, or provides information that could assist in proper vehicle service. The procedures should not be performed by 'do-it-yourselfers'. If you are not a Retailer, do not assume that a condition described affects your vehicle. Contact an authorized Land Rover service facility to determine whether this bulletin applies to a specific vehicle.

REPAIR PROCEDURE

REPLACE REAR BRAKE PADS



NOTE: Global Technical Reference (GTR) lookup sequence is as follows:
GTR Home > NAS > Model > Service Information > Model Year > Workshop Manual > 2: Chassis > 206: Brake System > 206-04: Rear Disc Brake

1. Refer to Workshop Manual (GTR) section 206-04: Rear Disc Brake (*70.40.03*) to remove the rear brake pads.



CAUTION: The adhesive strips covering the outboard pads must be removed prior to installation.

2. Remove the adhesive strips from the outboard pads.
(Figure 1)



NOTE: Ensure the outboard pad sticky shim can be seen when installed in the caliper.

3. Refer to Workshop Manual (GTR) section 206-04: Rear Disc Brake (*70.40.03*) to install the rear brake pads.

Figure 1

